- EV 7,4 kW charger
- LED indicator
- 5m cable
- Type 2 connector

Product ID	MEV07NNNN5T2
Charging mode	Level 2
Connector type	Type 2 connector with 5m cable
Charging control	Plug-and-Charge
Internet connection	No
External communication	RS485
IP protection	IP55
Impact strength	IK10
Display	No
LED indicator	LED color indicators
Communication protocol	-
Background functions	-
Reports	-
Standard and CE certificate	
Leakage protection	TypeB (AC30mB + DC6mA)
Mounting	Wall / Stand
Stand / ground mount	Available, not included
Cooling method	Natural Cooling
Power network configuration	TN / TT -> (3P+N+PE), TN / TT -> (1P+N+PE)
Efficiency	>99%
Power meter	No
AC power Input rating	1-phase 230V±20%
Rated frequency	50/60 Hz
Output current	32 A / 16 A
Output power	7.4 kW
DLM function	Available, CT not included
Storage temperature	40 to 75°C ambient
Operating temperature	30 to 55°C ambient
Operating humidity	Up to 95% non-condensing
Altitude	≤2000m
Electrical protection	Over/Under Voltage Protection, Over Load Protection, Short Circuit Protection, Earth Leakage Protection, Ground Protection, Over-temp Protection, Surge Protection
Dimensions mm	455 (h) x260 (w) x150 (d)
Weight kg	4,4
Warranty	18 months



