- EV 11 kW adaper
- LCD display
- 5m cable
- Type 2 connector

Charging modeLevel 2Connector typeType 2 connector with 5m cableCharging controlPlug-and-Charge, Start/stop touch adjustable between 6 - 16AIP protectionIP66Impact strengthIK08DisplayLCD 3.8"ReportsEnergy usage on diplayStandard and CE certificateCE certifiedLeakage protectionTypeA + DC6mAMountingWall (optional with bracket)Efficiency>99%Power meterIntegratedAC power Input rating3-phase 400V±20% / 1-phase 230VRated frequency50/60 Hz	button,
Charging controlPlug-and-Charge, Start/stop touch adjustable between 6 - 16AIP protectionIP66Impact strengthIK08DisplayLCD 3.8"ReportsEnergy usage on diplayStandard and CE certificateCE certifiedLeakage protectionTypeA + DC6mAMountingWall (optional with bracket)Efficiency>99%Power meterIntegratedAC power Input rating3-phase 400V±20% / 1-phase 230V	button,
adjustable between 6 - 16A IP protection IP66 Impact strength IK08 Display LCD 3.8" Reports Energy usage on diplay Standard and CE certificate CE certified Leakage protection TypeA + DC6mA Mounting Wall (optional with bracket) Efficiency >99% Power meter Integrated AC power Input rating 3-phase 400V±20% / 1-phase 230V	button,
IP protectionIP66Impact strengthIK08DisplayLCD 3.8''ReportsEnergy usage on diplayStandard and CE certificateCE certifiedLeakage protectionTypeA + DC6mAMountingWall (optional with bracket)Efficiency>99%Power meterIntegratedAC power Input rating3-phase 400V±20% / 1-phase 230V	
Impact strengthIK08DisplayLCD 3.8"ReportsEnergy usage on diplayStandard and CE certificateCE certifiedLeakage protectionTypeA + DC6mAMountingWall (optional with bracket)Efficiency>99%Power meterIntegratedAC power Input rating3-phase 400V±20% / 1-phase 230V	
DisplayLCD 3.8"DisplayLCD 3.8"ReportsEnergy usage on diplayStandard and CE certificateCE certifiedLeakage protectionTypeA + DC6mAMountingWall (optional with bracket)Efficiency>99%Power meterIntegratedAC power Input rating3-phase 400V±20% / 1-phase 230V	
ReportsEnergy usage on diplayStandard and CE certificateCE certifiedLeakage protectionTypeA + DC6mAMountingWall (optional with bracket)Efficiency>99%Power meterIntegratedAC power Input rating3-phase 400V±20% / 1-phase 230V	
Standard and CE certificate CE certified Leakage protection TypeA + DC6mA Mounting Wall (optional with bracket) Efficiency >99% Power meter Integrated AC power Input rating 3-phase 400V±20% / 1-phase 230V	
Leakage protectionTypeA + DC6mAMountingWall (optional with bracket)Efficiency>99%Power meterIntegratedAC power Input rating3-phase 400V±20% / 1-phase 230V	
Mounting Wall (optional with bracket) Efficiency >99% Power meter Integrated AC power Input rating 3-phase 400V±20% / 1-phase 230V	
Efficiency >99% Power meter Integrated AC power Input rating 3-phase 400V±20% / 1-phase 230V	
Power meter Integrated AC power Input rating 3-phase 400V±20% / 1-phase 230V	
AC power Input rating 3-phase 400V±20% / 1-phase 230V	
Rated frequency 50/60 Hz	′±20%
Output current 32 A / 16 A	
Output power 11 kW/ 7.4 kW/ 3.6 kW	
Storage temperature -40 to 75°C ambient	
Operating temperature -30 to 55°C ambient	
Operating humidity Up to 95% non-condensing	
Altitude ≤2000m	
Electrical protection Over Load Protection, Short Circuil Protection, Ground Protection, Ov Protection	
Dimensions mm 455 (h) x260 (w) x150 (d)	
Weight kg 4,5	
Warranty 24 months	





Accessories to mobile adapter	
Aluminium wall bracket	MEVA01NWPLATE
Extension 3P16A to 1P Shucko	MEVX01N3PWIRE
Cable holder for wall mount	MEVH01NHANDLE



Morek EV 11 kW EVSE mobile adapter

Use it when traveling or at home. Compact mobile charging adapter that should always be with every electric car.

Scan for more

More information about Morek EV chargers and discussions about EV user cases can be found from



ev.morek.eu