- EV 11 kW charger
- LED indicator
- 6,5m cable
- Type 2 connector

Product ID	MEV11NRNNN6T2
Charging mode	Level 2
Connector type	Type 2 connector with 5m cable
Charging control	RFID, Plug-and-Charge
Internet connection	No
External communication	No
IP protection	IP55
Impact strength	IK10
Display	No
LED indicator	LED color indicators
Communication protocol	-
Background functions	-
Reports	-
Standard and CE certificate	TUV certified
Leakage protection	TypeB (AC30mA + DC6mA)
Mounting	Wall / Stand
Stand / ground mount	Available, not included
Cooling method	Natural Cooling
Power network configuration	TN / TT -> (3P+N+PE), TN / TT -> (1P+N+PE)
Efficiency	>99%
Power meter	No
AC power Input rating	3-phase 400V±20% / 1-phase 230V±20%
Rated frequency	50/60 Hz
Output current	16 A
Output power	11 kW/ 3.6 kW
DLM function	No
Storage temperature	-40 to 75°C ambient
Operating temperature	-25 to 50°C ambient
Operating humidity	Up to 95% non-condensing
Altitude	≤2000m
Electrical protection	Over current protection, over voltage protection, under voltage protection, over temperature protection, leakage protection, unconnected PE ground protection.
Dimensions mm	455 (h) x260 (w) x150 (d)
Weight kg	5,9
Warranty	24 months





