

- **DC 180 kW fast charger**
- **7" LCD display**
- **LAN, 4G, RFID**
- **2 CCS2 connectors**

Product ID	MEV180DRENGxCCS
Charging mode	Level 3 / MODE 4 / CASE C
Connector type	CCS2 connectors
Number of connectors	2 (CCS2 + CCS2)
Charging control	APP, QR Code (optional), RFID
Internet connection	Ethernet / 4G
IP protection	IP54
Impact strength	IK10
Display	7-inch touch LCD
Display height mm	1265
Communication protocol	OCPP1.6J (OCPP2.0 ready)
Power Distribution	Yes
Reports	Full OCPP support
Certificate	CE certified
Standard	IEC61851-1 / IEC62196-3
Casing material	Galvanized steel
Cooling method	Forced Air Cooling
Power network configuration	TN-S/TN-C-S/TT
Peak efficiency	>95%
Power meters	Yes
AC power Input rating	AC 400 V (AC 323 V ~ AC 437 V)
Noise	≤60dB
Standby Power	≤99W
Output current	291A (0~342A)
Output power	180 kW (max)
DC output voltage range	150 V ~ 1000 V DC
DC output current	0 ~ 200 A
Power Limiting	Available
Storage temperature	-40 to 70°C ambient
Operating temperature	-25 to 55°C ambient
Operating humidity	5%~95% (no condensation)
Altitude	≤2000m
Electrical protection	Input Over/UnderVoltage Protection, Output Over Voltage Protection, Short-Circuit Protection, Over Current Protection
Dimensions mm	1700 (h) x800 (w) x600 (d)
Weight kg	355
Warranty	36 months



Morek EV 180 kW fast charger

Safe, reliable and efficient charging service while monitoring real-time charging status and progress.


Scan for more

More information about Morek EV chargers and discussions about EV user cases can be found from



ev.morek.eu

Creating a better future for You



N	Version	Description	Date
1	1.0.1	Morek EV/CDC	18.08.2023

Cabinet air outlet

Not included Connector

LED Display

Connector

Cabinet air inlet

LEFT VIEW

FRONT VIEW

RIGHT VIEW

MOREK		Code	MEV180DRENGXCCS	
Material coding	Unit	Material	Galvanized steel	
		DC 180kW 291A	Proportion	RAL9003
mm	mm	Projection logo	1:1	RAL1003
				RAL7024