Morek EV 22kW EVSE mobile adapter

Use it when traveling or at home. Compact and powerful mobile charging adapter that should always be with every electric car.

Product ID	MEV22DNNNN5T2
Charging mode	Level 2
Connector type	Type 2 connector with 5 m cable
Charging control	Plug-and-Charge, start/stop touch button, adjustable between 6 – 32A
IP protection	IP66
Impact strength	IK08
Display	LCD 3.8'
Reports	Energy usage on diplay
Standard and CE certificate	CE certified
Leakage protection	Type B AC 30mA + DC6mA
Mounting	Wall (optional with bracket)
Efficiency	>99%
Power meter	Integrated
AC power Input rating	3-phase 400V±20% / 1-phase 230V±20%
Rated frequency	50/60 Hz
Input current	32 A / 16 A
Output power	22kW – 2kW
Storage temperature	-40 to 80 °C ambient
Operating temperature	-25 to 50 °C ambient
Operating humidity	Up to 95% non-condensing
Altitude	≤2000m
Electrical protection	Over-current 1.125In, over- and under-voltage ±15%, over temperature ≥ 70°C, reduce to 6A to charge, and stop charging when >75°C
Dimensions mm	295 (h) x 160 (w) x 70 (d)
Weight kg	4,9







- AC 22kW charger
- LED indicator
- 5 m cable
- Type 2 connector
- Up to 110 km/h
- 1. EV and Power Connection
- 2. Power Charged
- 3. Time or Delay Charging
- 4. Current (Selected)
- 5. Fault Alarm
- 6. Unit of Power
- 7. Delay Charging Icon
- 8. Charging Cycle Display